

SAFETY DATA SHEET

1.	Identification	

Product identifier	BestSEP™		
Other means of identification	None.		
Recommended use	Not available.		
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.		
Manufacturer/Importer/Supplier	/Distributor information		
Manufacturer			
SUPPLIER	Best Slurry Solutions, LLC		
DETAILS	• (888) SLURRY7		
	(888) 758-7797		
	info@BestSlurrySolutions.com		
	BestSlurrySolutions.com		
Emergency phone number	Emergency 1.866.519.4752/1 760 476 3962		

Americs

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2B
	Carcinogenicity	Category 1A
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Causes skin irritation. Causes eye irritation. May cause cancer. through prolonged or repeated exposure.	
Precautionary statement		
Prevention	Obtain special instructions before use. Do not and understood. Do not breathe dust/fume/g	as/mist/vapors/spr

lazard statementCauses skin irritation. Causes eye irritation. May cause cancer. Causes damage to organs
through prolonged or repeated exposure.recautionary statementObtain special instructions before use. Do not handle until all safety precautions have been read
and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after
handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective
clothing/eye protection/face protection.ResponseIf on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.
Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get
medical advice/attention. Specific treatment (see on this label). If skin irritation occurs: Get
medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off
contaminated clothing and wash before reuse.Storage
DisposalStore locked up.Dispose of contents/container in accordance with local/regional/national/international regulations.

32.14% of the mixture consists of component(s) of unknown acute dermal toxicity.

3. Composition/information on ingredients

Mixtures			
Chemical name	Common name and synonyms	CAS number	%
TRADE SECRET*		Proprietary*	16
QUARTZ (SIO2)		14808-60-7	3 - < 5
TRADE SECRET*	*	Proprietary*	3.7
TRADE SECRET*		Proprietary*	3.3
CRISTOBALITE		14464-46-1	1 - < 3
Other components below repo	rtable levels		70 - < 80
*Designates that a specific chemi	cal identity and/or percentage of composition ha	as been withheld as a trade se	ecret.
Composition comments	Occupational Exposure Limits for impurities a occurring crystalline silica (not listed in Anne 4%.		
4. First-aid measures			
Inhalation	If exposed to excessive levels of dusts or fun cough or other symptoms develop. Move to f give oxygen by trained personnel. Call a phy	resh air. If not breathing, give	artificial respiration or
Skin contact	Immediately flush skin with running water for Get medical attention if irritation develops or advice/attention. Wash contaminated clothin	persists. If skin irritation occur	
Eye contact	Immediately flush eyes with plenty of water for present and easy to do. Continue rinsing. Get		
Ingestion	Have victim rinse mouth thoroughly with wate medical attention. Get medical attention if sy		nt does occur, seek
Most important symptoms/effects, acute and delayed	Irritation of eyes. Exposed individuals may ex irritation. May cause redness and pain. Prolo		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and tre Symptoms may be delayed.	eat symptomatically. Keep vict	im under observation.
General information	IF exposed or concerned: Get medical advice (show the label where possible). Ensure that involved, and take precautions to protect the	medical personnel are aware	
5. Fire-fighting measures			
Suitable extinguishing media	Dry chemical, CO2, water spray or regular fo	am.	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as th		
Specific hazards arising from the chemical	During fire, gases hazardous to health may b	be formed.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full p	protective clothing must be wo	rn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do	so without risk.	

Specific methods General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear Personal precautions, protective equipment and appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. emergency procedures Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Use standard firefighting procedures and consider the hazards of other involved materials.

Methods and materials for containment and cleaning up	Stop leak if you can do so without risk. Avoid the generation of dusts during clean-up. Sweep up or gather material and place in appropriate container for disposal.
	Large Spills: Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. Large spills may be neutralized with dilute alkaline solutions of soda ash, or lime.
Environmental precautions	Do not let product enter drains. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. No special restrictions on storage with other products. Store in original tightly closed container. No special storage conditions required. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	PEL	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR 191	0.1000)		
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
Impurities	Туре	Value	Form
INERT OR NUISANCE DUSTS	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Valu	es		
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

US. NIOSH: Pocket Guide			_
Components	Туре	Value	Form
CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
QUARTZ (SIO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
Biological limit values	No biological exposure limits noted for the	e ingredient(s).	
Exposure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
Appropriate engineering controls	If engineering measures are not sufficient to maintain concentrations of dust particulates below the OEL, suitable respiratory protection must be worn. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits. Provide eyewash station. Eye wash fountain and emergency showers are recommended.		
Individual protection measures	s, such as personal protective equipment		
Eye/face protection	Wear dust goggles. Eye wash fountain is	recommended.	
Skin protection			
Hand protection	Wear appropriate chemical resistant glov	es. Impervious butyl rubber	gloves.
Other	Wear appropriate chemical resistant cloth of protective coveralls and long sleeves is clothing before re-use.		
Respiratory protection	Use a particulate filter respirator for partic Exposure Limit.	culate concentrations excee	ding the Occupational
Thermal hazards	Wear appropriate thermal protective cloth	ning, when necessary.	
General hygiene considerations	Observe any medical surveillance require measures, such as washing after handling smoking. Routinely wash work clothing a	g the material and before e	ating, drinking, and/or

9. Physical and chemical properties

••••••••••••••••••••••••••••••••••••••		
Appearance		
Physical state	Solid.	
Form	Powder.	
Color	Tan.	
Odor	None.	
Odor threshold	Not available.	
рН	3.5	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	Not available.	
Flash point	Not available.	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	0.00004 hPa estimated	
Vapor density	Not available.	

Relative density	Not available.
Solubility(ies)	
Solubility (water)	100 %
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	2.53 g/cm3 estimated
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Percent volatile	0 % estimated
Specific gravity	2.53 estimated
VOC	CARB
10. Stability and reactivit	у

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Stable at normal conditions.
Possibility of hazardous reactions	Will not occur.
Conditions to avoid	Contact with incompatible materials. None known.
Incompatible materials	None known.
Hazardous decomposition products	None known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity

Not known. May cause skin and eye irritation.

Components	Species	Test Results	
CRISTOBALITE (CAS 14464-46-	1)		
Acute			
Oral			
LD50	Rat	> 22500 mg/kg	
TRADE SECRET			
Acute			
Inhalation			
LC50	Rat	2.3 mg/l, 2 Hours	
Oral			
LD50	Rat	4090 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes eye irritation.		
Respiratory or skin sensitizatio	n		
Respiratory sensitization	Not a respiratory sensitizer.		
Material name: BestSEP™		SD	os us

Skin sensitization	This product is not expected	to cause skin sensitization	
Germ cell mutagenicity	This product is not expected to cause skin sensitization. No data available to indicate product or any components present at greater than 0.1% are		
	mutagenic or genotoxic.		
Carcinogenicity	inhaled from occupational sc overall evaluation, IARC noto circumstances studied. Carc crystalline silica or on extern polymorphs." (IARC Monog humans, Silica, silicates dus 2003, SCOEL (the EU Scien main effect in humans of the sufficient information to conc silicosis (and, apparently, no in the ceramic industry). The risk" (SCOEL SUM Doc 94 protection against silicosis c occupational exposure limits	bonal Agency for Research on Cancer) concluded that crystalline silica bources can cause lung cancer in humans. However in making the ed that "carcinogenicity was not detected in all industrial sinogenicity may be dependent on inherent characteristics of the hal factors affecting its biological activity or distribution of its raphs on the evaluation of the carcinogenic risks of chemicals to st and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June tific Committee on Occupational Exposure Limits) concluded that the e inhalation of respirable crystalline silica dust is silicosis. "There is clude that the relative risk of lung cancer is increased in persons with ot in employees without silicosis exposed to silica dust in quarries and erefore, preventing the onset of silicosis will also reduce the cancer I-final, June 2003) According to the current state of the art, worker an be consistently assured by respecting the existing regulatory s. May cause cancer. Occupational exposure to respirable dust and hould be monitored and controlled.	
IARC Monographs. Overall	Evaluation of Carcinogenicit	у	
CRISTOBALITE (CAS 14		1 Carcinogenic to humans.	
QUARTZ (SIO2) (CAS 14	4808-60-7) d Substances (29 CFR 1910.	1 Carcinogenic to humans.	
CRISTOBALITE (CAS 14		Cancer	
QUARTZ (SIO2) (CAS 14	,	Cancer	
	ogram (NTP) Report on Carci	nogens	
CRISTOBALITE (CAS 14		Known To Be Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.	
QUARTZ (SIO2) (CAS 14 Reproductive toxicity		Known To Be Human Carcinogen. to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Causes damage to organs the	hrough prolonged or repeated exposure.	
Aspiration hazard	Not an aspiration hazard.		
Chronic effects	inhaled from occupational so overall evaluation, IARC note circumstances studied. Carc crystalline silica or on extern polymorphs." (IARC Monog humans, Silica, silicates dus In June 2003, SCOEL (the E that the main effect in human "There is sufficient informatio persons with silicosis (and, a quarries and in the ceramic is the cancer risk" (SCOEL S According to the current stat	 bonal Agency for Research on Cancer) concluded that crystalline silica bources can cause lung cancer in humans. However in making the ed that "carcinogenicity was not detected in all industrial cinogenicity may be dependent on inherent characteristics of the hal factors affecting its biological activity or distribution of its raphs on the evaluation of the carcinogenic risks of chemicals to and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) EU Scientific Committee on Occupational Exposure Limits) concluded ns of the inhalation of respirable crystalline silica dust is silicosis. on to conclude that the relative risk of lung cancer is increased in apparently, not in employees without silicosis exposed to silica dust in industry). Therefore, preventing the onset of silicosis will also reduce SUM Doc 94-final, June 2003) te of the art, worker protection against silicosis can be consistently xisting regulatory occupational exposure limits. Causes damage to 	
	organs through prolonged or exposure may cause chronic respirable) and respirable cr	r repeated exposure. Prolonged inhalation may be harmful. Prolonged c effects. Occupational exposure to nuisance dust (total and ystalline silica should be monitored and controlled.	
12. Ecological information			
Ecotoxicity		have been identified as having potential environmental concerns.	
Components	Species	Test Results	
TRADE SECRET			
		· · · · · · · · · · · · · · · · · · ·	

Bluegill (Lepomis macrochirus)

Material name: BestSEP™

Fish

LC50

300 mg/l, 96 hours

Components	Species	Test Results		
	Fish	<= 10 mg/l		
Persistence and degradability	No data is available on the degradability of this product.			
Bioaccumulative potential	No data available.			
Mobility in soil	No data available.			
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.			
13. Disposal considerations				
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.			
Local disposal regulations	Dispose in accordance with all applicable	e regulations.		
Hazardous waste code	The waste code should be assigned in di disposal company.	scussion between the user, the producer and the waste		
Waste from residues / unused products		ations. Empty containers or liners may retain some ontainer must be disposed of in a safe manner (see:		
Contaminated packaging	, , , ,	duct residue, follow label warnings even after container is en to an approved waste handling site for recycling or		

14. Transport information

DOT

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

OSHA Process Safety Standard: This material is not known to be hazardous by the OSHA Highly Hazardous Process Safety Standard, 29 CFR 1910.119. This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7) CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7) CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7) CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7)

Cancer Cancer lung effects lung effects immune system effects immune system effects kidney effects kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

California Proposition 65



WARNING: This product can expose you to QUARTZ (SIO2), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Listed: October 1, 1988

QUARTZ (SIO2) (CAS 14808-60-7) US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRISTOBALITE (CAS 14464-46-1) QUARTZ (SIO2) (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	17-March-2015
Revision date	22-August-2018
Version #	12
Further information	This safety datasheet only contains information relating to safety and does not replace any product information or product specification.
HMIS® ratings	Health: 3* Flammability: 0 Physical hazard: 0
NFPA ratings	Health: 2 Flammability: 0 Instability: 0

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The manufacturer expressly does not make any representations, warranties, or guarantees as to its accuracy, reliability or completeness nor assumes any liability, for its use. It is the user's responsibility to verify the suitability and completeness of such information for each particular use.

Third party materials: Insofar as materials not manufactured or supplied by this manufacturer are used in conjunction with, or instead of this product, it is the responsibility of the customer to obtain, from the manufacturer or supplier, all technical data and other properties relating to these and other materials and to obtain all necessary information relating to them. No liability can be accepted in respect of the use of this product in conjunction with materials from another supplier. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. CETCO Energy Services Company, an MTI Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Revision information

Composition / Information on Ingredients: Ingredients